



NOISE / VIBRATION
& HARSHNESS

QuietWrap™ 3002

Product Highlights

- Operating Temperature up to +150°C (+302°F)
- Self curling wrappable design
- Excellent abrasion resistance
- Flexible
- Lightweight
- Aesthetic solution

Typical Applications

- Body wiring harnesses
- Instrument panel harnesses
- Engine compartment harnesses
- Modular wire harnesses
- Tube, hose, and cable assemblies



Our manufacturing sites are certified ISO 9001, ISO/TS 16949, or AS/EN 9100, ISO 14001 and ISO 45001 (Selected Sites)

QW3002_03062020



QuietWrap™ 3002 is an acoustic laminate composed of a abrasion resistant fabric and noise damping foam. A fully backed adhesive system provides fixation for challenging geometries and locations where traditional methods struggle.

The combination of fabric and foam provides excellent noise suppression while offering a high level of abrasion protection. QuietWrap 3002 is more durable than standard foam.

Performance Data – QuietWrap™ 3002

Property	Test Method	Result
Temperature Rating	240 hours at +150°C rating	Pass +150°C (+302°F)
Low Temperature Flexibility	BH100-016A	Pass -40°C (-40°F)
Flammability	SAE J369	Self-extinguishing
Fluid Resistance	BH100-003B	Pass
Noise Suppression	SAE J2192	Rubbing : > 14dB Rattling : > 50dB

All numeric performance data shows average or typical values. Please consult your sales representative for product drawings, test reports and OEM approvals.

Availability

QuietWrap 3002 is a customizable product and is available in various designs to meet specific application requirements. Color is black. Please contact your sales representative for availability.



United States: (1) 800 926 2472
México: (52) 442 101 8100
Brazil: (55) 19 3116 1600
France: (33) 3 44 39 06 06
Japan: (81) 45 330 0300
China: (86) 21 6182 7560
Thailand: (66) 35 276 400
Korea: (82) 44 861 6368
India: (91) 124 4784565

For informational purposes only. Tenneco makes no warranties as to the accuracy or completeness of the information provided herein and disclaims any liability in connection with its use. Tenneco's only obligations are those provided in its terms and conditions of sale for this product, and Tenneco will not be liable for any damages, whether direct or indirect, arising out of the use or misuse of this product. Users should undertake their own evaluations to determine the suitability of the product for specific applications.

©2019 Tenneco Systems Protection, manufacturer of Bentley-Harris protection products.

www.tennecosp.com