



ABRASION/MECHANICAL

TwistWrap™ 2403

Product Highlights

- Operating temperature up to +150°C (+302°F)
- Quick and easy cable bundling
- Extremely lightweight
- Good abrasion protection
- Low profile

Typical Applications

- Instrument panel harnesses
- Door harnesses
- Floor harnesses
- Engine compartment harnesses



Our manufacturing sites are certified ISO 9001, ISO/TS 16949, or AS/EN 9100, and ISO 14001

TW2403_07202017



TwistWrap™ 2403 is a self-wrapping sleeve designed to enable fast and easy wire harness bundling. Woven of both monofilament and multifilament polyester yarns the product is both flexible and lightweight. The polyester construction eliminates problems associated with trapped heat and humidity and also eliminates operator skin irritation during assembly. The combination of materials also enables the product to provide a level of abrasion protection for the wire bundle.

TwistWrap 2403 maintains a circular profile when flexed and its unique design easily allows for breakouts and installation over completed assemblies.

BentleyHarris®
Protection Products

Performance Data – TwistWrap™ 2403

Property	Test Method	Result
Temperature Rating	240 hrs at +175°C (+150°C rating)	Pass +150°C (+302°F)
Low Temperature Flexibility	BH100-016A	Pass -70°C (-94°F)
Flammability	SAE J369	Self-extinguishing
Fluid Resistance	BH100-003B	Pass
Melt Temperature	ASTM D3418	+245°C to +265°C (+473°F to +509°F)

All numeric performance data shows average or typical values. Please consult your sales representative for product drawings, test reports and OEM approvals.


Construction and Typical Product Characteristics

Warp Yarn: Polyester (PET) Multifilament

Fill Yarn: Polyester (PET) Monofilament

Availability

TwistWrap 2403 is available in a range of sizes and cut to your specification. Standard color is black. Please contact your sales representative for availability.



End view of TwistWrap 2403 illustrating self-wrapping construction.

The information and illustrations given herein are believed to be reliable. Federal-Mogul makes no warranties as to their accuracy or completeness and disclaims any liability in connection with their use. Federal-Mogul's only obligations are those in the standard term of sale for this product and Federal-Mogul will not be liable for any consequential or other damages arising out of the use or misuse of this product. Users should make their own evaluations to determine the suitability of the product for specific applications.

©2008 Federal-Mogul Systems Protection, manufacturer of Bentley-Harris protection products.

 **FEDERAL
MOGUL**
Systems Protection

USA: (1) 800 926 2472
Europe: (33) 3 44 39 06 06
Japan: (81) 45 479 0201
China: (86) 21 6182 7688

www.federalmogul.com/sp